











pipeline transport of viscous crude oils. In SPE Annual Technical Conference and Exhibition, 2-5 Oct (Paper SPE 18218).  
<http://dx.doi.org/10.2118/18218-MS>.

[12] Sanchez, L. E. and Zakin, J. L. (1994). Transport of viscous crudes as concentration oil-in-water emulsions. *Ind. Engng Chem. Res.* 33, 3256-3261.

[13] Schubert, H. and Armbruster, H. (1992). Principles of formation and stability of emulsions. *International Chemical Engineering*, 32(1), 14-28.

[14] Asomaning, S. and Watkinson, A.P. (1999). Deposit formation by asphaltene-rich heavy oil mixtures on heat transfer surfaces. *Proceedings of the International Conference on Mitigation of Heat Exchanger Fouling and Its Economic and Environmental Implications*, July, 1999 (pp. 283-287). Banff, Alberta, Canada: Banff Centre.

[15] Lee, R. F. (1999). Agents which promote and stabilize water-in-oil emulsions. *Spill Science & Technology Bulletin*, 5(2), 117-126.

[16] Ali, M.F. and Alqam, M.H. (2000). The role of asphaltenes, resins and other solids in the stabilization of water in oil emulsions and its effects on oil production in Saudi oil fields. *Fuel* 79, 1309 – 1316.

[17] Gafonova, O.V. (2000). Role of Asphaltenes and Resins in the Stabilization of Water-in-Hydrocarbon Emulsions. The University of Calgary: MSc. Thesis.

[18] Kilpatrick, P.E., and Spiecker, P.M. (2001). Asphaltene Emulsion. In J. Sjöblom (Ed.), *Encyclopedic handbook of emulsion technology* (pp. 707-730). New York: Marcel Dekker

[19] Bennett, C.A., Appleyard, S., Gough, M., Hohmann, R.P., Joshi, H.M., King, D.C. Stomierowski, S.E. (2006). Industry recommended procedures for experimental crude oil preheat fouling research. *Heat Transfer Eng.*, 27, 28-35.

[20] Krieger, I.M. and Dougherty, T.J. (1959). A mechanism for non-Newtonian flow in suspensions of rigid spheres. *Trans. Soc. Rheol.* 3, 137–152.

[21] Wong, S.F., Law, M.C., Samyudia, Y., and Dol, S.S. (2015). Rheology study of water-in-crude

oil emulsions. *Chemical Engineering Transactions* 45, 1411-1416.

[22] Otsubo, Y. and Prud'homme, R.K. (1994). Effect of drop size distribution on the flow behaviour of oil-in-water emulsions. *Rheol. Acta*, 33, 303–306.

[23] Zaki, N. (1997). Surfactant stabilized crude oil-in-water emulsions for pipeline transportation of viscous crude oils. *Colloids Surf., A Physicochem. Eng. Asp.*, 125 (1), 19–25.

[24] Kokal, S. (2005). Crude-oil emulsions: A state-of-the-art review. *SPE Production and Facilities*, SPE 77497-PA.  
<http://dx.doi.org/10.2118/77497-PA>.

[25] Ashrafizadeh, S.N. and Kamran, M. (2010). Emulsification of heavy crude oil in water for pipeline transportation. *Journal of Petroleum Science and Engineering*, 71, 205 – 211.

[26] Becher, P. (1955). Principles of emulsion technology. New York: Reinhold